

# Terminal LX700

## Ruggedized Smartphone



8-Core 2GHz CPU

Android 9.0, 4G+64G

LTE+DMR Dual Mode

IP67 Protection Grade

0.2" Fingerprint Identification

The LX700 from BTI wireless is a high-end broadband handheld terminal with a large screen, which can provide powerful functions for multiple service transmission. The device is IP67 rated waterproof and dustproof, equipped with Android 9.0 operating system and 8-core CPU processor. It can be widely used in various industry scenarios, with excellent compatibility and scalability.

## HARDWARE SPECIFICATIONS

<b>Walkie-talkie</b>	4 Watts DMR+ Analog, UHF
<b>Display</b>	4.0-inch IPS HD hard screen
<b>Touch Panel</b>	5 points capacitive screen Supports rainwater operation
<b>Glove Wearing Touch</b>	Supported
<b>Resolution</b>	640*1136 pixels TFT LCM
<b>Sim</b>	Dual SIM, Dual standby, the third SIM card for private network (Optional)
<b>Network</b>	GSM, WCDMA, EVDO, TD-SCDMA, TDD/FDD-LTE
<b>Band</b>	2G:GSM850/900/1800/1900 3G:WCDMA850/900/1900/2100 LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B17/B20 LTE-TDD: B38/B39/B40/B41 Band28A/28B can be customized individually
<b>OS</b>	Android 9.0
<b>CPU</b>	MTK6763, Octa core, 2.0 GHz
<b>Memory</b>	4GB RAM + 64GB ROM
<b>Micro SD Card</b>	Supports up to 128GB
<b>Battery</b>	2500mAh@7.4V (Standard)
<b>Color</b>	Black
<b>Size</b>	148 x 64 x 30.3 mm   5.83 x 2.52 x 1.19 in (2500mAh battery) 148 x 64 x 35 mm   5.83 x 2.52 x 1.38 in (4000mAh battery)
<b>Weight</b>	430 g   0.95 lbs
<b>SOS</b>	Supported
<b>Channel Knob</b>	Supported
<b>PTT</b>	Optional, Push-to-Talk over two-way radio
<b>POC</b>	Supported, Push-to-Talk over Cellular/ Wi-Fi
<b>Programmable Key</b>	Supported, Customer can customize the shortcut key for special function purposes by software
<b>GNSS</b>	GPS/ BEIDOU/ GLONASS
<b>Charging Dock</b>	Supported
<b>Quick Charge</b>	Supports 2A quick charge
<b>Clip</b>	Supported
<b>Mic</b>	Dual mic to anti-noise
<b>IP Class</b>	IP67
<b>Sensors</b>	Gravity, Gyro, Distance sensor, Light sensor, 3D accelerator, Pressure sensor
<b>FM</b>	Supported
<b>NFC</b>	Optional, 13.56 MHZ Contactless interface modem - ISO/IEC 18092 Active/ Passive communication (Active/ Passive initiator and target) - ISO/IEC 14443 A and B Reader/ Writer - ISO/IEC 15693 Reader/ writer - Sony FeliCa Reader/ Writer - Topaz Reader/ Writer - KOVIO (RF Barcode) Reader - ISO/IEC 14443 A and B card emulation

	- Sony FeliCa card emulation - ISO/IEC 15693 card emulation
<b>Speaker</b>	2 Watts
<b>Working Temperature</b>	-20 °C ~ +60 °C   -4 °F ~ +140 °F
<b>Storage Temperature</b>	-20 °C ~ +70 °C   -4 °F ~ +158 °F

## APPEARANCE



COMPONENT SPECIFICATIONS	
Camera	Front camera: 5mega pixels Rear camera: 13mega pixels
Picture Size	Up to 4096*3072 pixels
Flash LED/Torch	1 flash led, 200 Lumina
Video Record	1920*1080 recording, 30fps
External Camera	Supported (optional)
External Palm Mic	Supported (optional)
WLAN	WIFI 802.11 a/b/g/n, 2.4G/5.8G
Data Port	USB 2.0
USB Port	20 pin multiple port, 2A charge
OTG	Supported
Bluetooth	Bluetooth 4.0

STANDARD ACCESSORIES
1 x Battery, 2500mAh@7.4V (Standard)
1 x Walkie Talkie Antenna
1 x Data Cable
1 x Manual
1 x Charger Adapter

PRODUCT CERTIFICATIONS
RoHS Certification
CCC Certification
CTA Certification
Intrinsically Safe Certification
Coal Safety Certification
CE Certification
FCC Certification

Contact Us

[www.btiwireless.com](http://www.btiwireless.com)[sales@btiwireless.com](mailto:sales@btiwireless.com)